



CEE 7/XXVI

A60 | 100.0%  $\Phi$ : 300 lm



60 x 60 cm  $\Phi$ : 300 lm

Em: 522 lx  
Emax: 806 lx  
Emin: 199 lx



light source  
work equipment  
connected load  
secondary tension  
power consumption  
sec. power consumption  
standby  
power factor  
luminous flux  
luminous efficiency  
light type/-color  
colour temperatur  
color rendering index  
light distribution  
direct ratio  
beam angle  
chromaticity tolerance LED  
glare control  
system of protection  
class of protection  
technology  
operation  
housing  
Light source cover  
arm  
balance of articulation joints  
weight (net)  
mains lead  
fastening  
energy efficiency class  
special features

LED module  
electronic plug-in transformer  
100 - 240 V; AC; 50 Hz; 60 Hz  
5 V  
ca. 4 W  
ca. 3,5 W  
ca. 0,3 W  
env. 0,97  
approx. 300 lm  
approx. 96 lm/W  
cold white  
approx. 4.000 K  
CRI  $\geq$  80  
direct  
approx. 100 %  
73°  
< 3 SDCM  
screen  
IP 20  
II with plug-in power supply, III without plug-in  
power supply  
continuously dimmable;  
Gleichspannungssteuerungssigna  
push button  
plastic; untreated; umbra grey  
Polycarbonate (PC); satine  
tubular aluminium section; anodized; tubular  
section upright; titanium  
none  
ca. 1 kg  
ca. 1,85 m; mains plug; CEE 7/XXVI  
adaptor (accessory); table clamp (accessory); table  
base  
E  
push button in luminaire head